


TECHNICAL SPECIFICATION



CONSTRUCTION

MACHINE GAUGE

PILE HEIGHT ISO 1766

TUFT DENSITY ISO 1763

PILE WEIGHT

TOTAL CARPET WEIGHT ISO 8543

CARPET THICKNESS ISO 1765

WIDTH

PLUS

1/10th Gauge

7 mm

139,500 tufts/m²

1,152 gms/m²

34 oz/yd²

1,930 gms/m²

10.2 mm

4 & 5 metre

ULTRA

1/10th Gauge

9 mm

156,940 tufts/m²

1,627 gms/m²

48 oz/yd²

2,407 gms/m²

12 mm

4 & 5 metre



COMPOSITION

PILE CONTENT ISO 1833

PRIMARY BACKING

SECONDARY BACKING

100% Excellon Polypropylene

Woven Polypropylene

Woven Secondary

100% Excellon Polypropylene

Woven Polypropylene

Woven Secondary



PERFORMANCE

SUITABILITY

WIRA ABRASION TEST PD 6527: Clause 17

STATIC LOADING ISO 3416

DYNAMIC LOADING ISO 2094

TUFT ANCHORAGE ISO 4919

Heavy Domestic / Medium Contract

Exceeds 36,800 Rubs

25.7% Thickness Loss after 24 hrs recovery

31.8% Thickness Loss after 1,000 impacts

Above 1.5 kg

Extra Heavy Domestic / Medium Contract

Exceeds 50,000 Rubs

24% Thickness loss after 24 hrs recovery

32% Thickness loss after 1,000 impacts

Above 1.4 kg



COLOUR FASTNESS

LIGHT FASTNESS ISO 105-B02

WET FASTNESS ISO 105-E01

SHAMPOO FASTNESS BS 1006: UK-TB

4/5 on all colours

4/5 on all colours

4/5 on all colours

4/5 on all colours

4/5 on all colours

4/5 on all colours



THERMAL VALUE

TOG VALUE ISO 5085-1

THERMAL RESISTANCE

1.4 Tog

0.14 m² k/w

1.5 Tog

0.15 m² k/w



FLAMMABILITY

CE MARK RATING

METHENAMINE PILL TEST ISO 6925

Efl

Pass

Efl

Pass



CHEMICAL IMPACT CE

FORMALDEHYDE

E1

E1



BIOLOGICAL ATTACK

MOTH / INSECT RESISTANT

Insect & rot proof

Insect & rot proof



ANTI STATIC

-0.2 kv (Requirement less than +2.0kv)

-0.2 kv (Requirement less than +2.0kv)

GENERAL INFORMATION

Installation - In all contract locations an 'all-over' stick down method is recommended to BS 5325 (1983). If underlay is required it should be of a firm and unyielding type and where installed in larger contract areas the carpet should be power stretched. For quantity orders requiring colour matching, please state at time of ordering.

Maintenance - To maintain your carpet's appearance it is recommended that it is vacuumed at least three times per week, to remove particles of dirt and dust. An upright vacuum with beater bar and brush is recommended for use with cut pile carpets. Please note, over time, regular foot traffic will flatten the pile surface in the main walkways, causing areas of differential wear.

These areas will appear lighter or shaded in comparison to the less frequently used parts. This shading / tracking or flattening happens to all carpets with a pile surface and as such is not accepted as the basis for any complaint. Similarly Pile Reversal (or watermarking) is a phenomenon that can affect all cut pile carpets and as such is not accepted as a manufacturing fault.

Matching - This sample may not be from the same production batch as current stock and therefore should be used as a guide and not as an exact match. Equally matching between 5 metre and 4 metre widths cannot be guaranteed.

Important - Minimum order length is 1.5 metres.